

PRO SERIES BULK COAXIAL CABLE



BULK COAX CABLE

SPOOLED CABLE • 500 Ft spools standard •
Special lengths & volume purchases available

Part No.	Length	Color	Dielectric	Conductor	Braid	Impedance
PRO58U-500	500 FT	BLACK	SOLID PE - .116	20 GA SOLID	95% BARE COPPER	50 Ohm
PRO58U-1000	1000 FT	BLACK	SOLID PE - .116	20 GA SOLID	95% BARE COPPER	50 Ohm
PRO58AU-500	500 FT	BLACK	SOLID PE - .116	20 GA (19X33) STRANDED	95% BARE COPPER	50 Ohm
PRO58AU-1000	1000 FT	BLACK	SOLID PE - .116	20 GA (19X33) STRANDED	95% BARE COPPER	50 Ohm
PRO59AU-500	500 FT	BLACK	SOLID PE - .116	20 GA (19X33) STRANDED	85% BARE COPPER	75 Ohm
PRO59AU-1000	1000 FT	BLACK	SOLID PE - .116	20 GA (19X33) STRANDED	85% BARE COPPER	75 Ohm
PRO8X-500	500 FT	GRAY	FOAM PE - .155	16 GA (19X28) STRANDED	95% BARE COPPER	50 Ohm
PRO8X-1000	1000 FT	GRAY	FOAM PE - .155	16 GA (19X28) STRANDED	95% BARE COPPER	50 Ohm
PRO8XB-500	500 FT	BLACK	FOAM PE - .155	16 GA (19X28) STRANDED	95% BARE COPPER	50 Ohm
PRO8XB-1000	1000 FT	BLACK	FOAM PE - .155	16 GA (19X28) STRANDED	95% BARE COPPER	50 Ohm
PRO8XC-500	500 FT	CLEAR	FOAM PE - .155	16 GA (19X28) STRANDED	95% BARE COPPER	50 Ohm
PRO8XC-1000	1000 FT	CLEAR	FOAM PE - .155	16 GA (19X28) STRANDED	95% BARE COPPER	50 Ohm
PROS8XC-500	500 FT	CLEAR	FOAM PE - .155	16 GA (19X28) STRANDED	96% TINNED COPPER	50 Ohm
PROS8XC-1000	1000 FT	CLEAR	FOAM PE - .155	16 GA (19X28) STRANDED	96% TINNED COPPER	50 Ohm
PROSD8XC-500	500 FT	CLEAR	FOAM PE - .155	16 GA (19X28) STRANDED	96% TINNED COPPER	TRUE 75 Ohm
PROSD8XC-1000	1000 FT	CLEAR	FOAM PE - .155	16 GA (19X28) STRANDED	96% TINNED COPPER	TRUE 75 Ohm
PRO8UB-500	500 FT	BLACK	SOLID PE - .146	13 GA (7X21) STRANDED	95% BARE COPPER	50 Ohm
PRO174-1000	1000 FT	BLACK	SOLID PE - .060	26 GA (7X34) STRANDED	95% BARE COPPER	50 Ohm
PRO213-500	500 FT	BLACK	SOLID PE - .285	20 GA SOLID	100% FOIL & 95% COPPER	50 Ohm