#### **PRO SERIES**

Length

12 IN

18 IN

3 FT

6 FT

9 FT

12 FT

18 FT

20 FT

21 FT

25 FT

50 FT

75 FT

100 FT

Part No.

PR1-8X

PR3-8X

PR6-8X

PR9-8X

PR12-8X

PR18-8X

PR20-8X

PR21-8X

PR25-8X

PR50-8X

PR75-8X

PR100-8X

PR1.5-8X

#### **RG8X CABLE**

MINI 8 • Bare copper stranded center

conductor • High quality soldered PL259

or lug connectors • 95% bare copper braid • Foam dielectric • Hand soldered

connections • 100% Tested • Add (L) to

end of model number for lug connector •

Available in gray, black (B) or clear (C)

MADE IN U. S.



#### **RG8X CABLE W/ REMOVABLE PL259**

MINI 8 • Bare copper stranded center conductor • High quality soldered PL259 on one end and a female FME connector on the other • High quality FME to UHF adapter (NIP-13) included • 95% bare copper braid • Foam dielectric • Hand soldered connections • 100% Tested • Replace (N13) with (FME) to exclude the NIP-13 adapter 
Available in gray or black (B)

#### **PRO SERIES**

Part No.	Length
PR3-8XN13	3 FT
PR6-8XN13	6 FT
PR9-8XN13	9 FT
PR12-8XN13	12 FT
PR18-8XN13	18 FT
PR21-8XN13	21 FT
PR25-8XN13	25 FT
PR50-8XN13	50 FT
PR75-8XN13	75 FT
PR100-8XN13	100 FT

#### **S8X CABLE**

SUPER MINI 8 • Tin plated copper stranded center conductor • Teflon dielectric soldered PL259 connectors • 96% tin plated copper braid • Foam dielectric • Hand soldered connections • 100% Tested • Add (L) to end of model number for lug connector • Available in clear jacket only

Part No.	Length
PR3-S8X	3 FT
PR6-S8X	6 FT
PR9-S8X	9 FT
PR12-S8X	12 FT
PR18-S8X	18 FT
PR20-S8X	20 FT
PR21-S8X	21 FT
PR25-S8X	25 FT
PR50-S8X	50 FT
PR75-S8X	75 FT
PR100-S8X	100 FT







### S8X CABLE W/ **REMOVABLE PL259**

SUPER MINI 8 • Tin plated copper stranded center conductor • High quality soldered PL259 on one end and a female FME connector on the other • High quality FME to UHF adapter (NIP-13) included • 96% tin plated copper braid • Foam dielectric • Hand soldered connections • 100% Tested • Replace (N13) with (FME) to exclude the NIP-13 adapter • Available in clear jacket only

#### **PRO SERIES**

Part No.	Length
PR3-S8XN13	3 FT
PR6-S8XN13	6 FT
PR9-S8XN13	9 FT
PR12-S8XN13	12 FT
PR18-S8XN13	18 FT
PR21-S8XN13	21 FT
PR25-S8XN13	25 FT
PR50-S8XN13	50 FT
PR75-S8XN13	75 FT
PR100-S8XN13	100 FT

#### SD8X CO-PHASE CABLE

SUPER DUAL MINI 8 • True 75 Ohm impedance • Tin plated copper stranded conductor • Teflon dielectric soldered PL259 connectors • 96% tin plated copper braid • Foam dielectric • Hand soldered connections • 100% Tested • Add (L) to end of model number for lug connector • Available in clear jacket only

#### **PRO SERIES**

Part No.	Length
PR9-SD8X	9 FT
PR12-SD8X	12 FT
PR18-SD8X	18 FT
PR21-SD8X	21 FT



MADE IN

S

### SD8X CO-PHASE CABLE W/ REMOVABLE PL259

SUPER DUAL MINI 8 • True 75 Ohm impedance • Tin plated copper stranded conductor • • High quality soldered PL259 on one end and two female FME connectors on the other ends • Two high quality FME to UHF adapters (NIP-13) included • 96% tin plated copper braid • Foam dielectric • Hand soldered connections • 100% Tested • Replace (N13) with (FME) to exclude the NIP-13 adapters • Available in clear jacket only

Part No.	Length
PR9-SD8XN13	9 FT
PR12-SD8XN13	12 FT
PR18-SD8XN13	18 FT
PR21-SD8XN13	21 FT

#### PRO SERIES


#### **RG8U CABLE**



LOW LOSS RG8U • Bare copper stranded center conductor • High quality soldered PL259 • 95% bare copper braid • Foam dielectric • Hand soldered connections • 100% Tested • Available in black jacket only

Part No.	Length
1.5RG8UB	18 IN
3RG8UB	3 FT
6RG8UB	6 FT
9RG8UB	9 FT
12RG8UB	12 FT
18RG8UB	18 FT
20RG8UB	20 FT
21RG8UB	21 FT
25RG8UB	25 FT
50RG8UB	50 FT
75RG8UB	75 FT
100RG8UB	100 FT

U.S.A.



HIGH QUALITY RG213 • Bare copper stranded center conductor • High quality soldered PL259 or TNC connectors • 95% bare copper braid • Polyethylene dielectric • Hand soldered connections • 100% Tested • Add (T) to the end of model number for TNC connector • Available in black jacket only

#### **PRO SERIES**

Part No.	Length
3RG213	3 FT
6RG213	6 FT
9RG213	9 FT
12RG213	12 FT
18RG213	18 FT
21RG213	21 FT
25RG213	25 FT
50RG213	50 FT
75RG213	75 FT
100RG213	100 FT

U.S.A.

#### **RG58 CABLE**





HIGH QUALITY RG58 • Bare copper stranded center conductor • High quality soldered PL259 or lug connectors • 95% bare copper braid • Polyethylene dielectric • Hand soldered connections • 100% Tested • Replace (PL) with (L) to end of model number for lug connector • Available in black jacket only

Part No.	Length
803PL	3 FT
806PL	6 FT
809PL	9 FT
812PL	12 FT
818PL	18 FT
820PL	20 FT
821PL	21 FT
825PL	25 FT
850PL	50 FT
875PL	75 FT
8100PL	100 FT



### RG58 CABLE WITH PL259 & FME

HIGH QUALITY RG58 • Bare copper stranded center conductor • High quality soldered PL259 and female FME • 95% bare copper braid • Polyethylene dielectric • Hand soldered connections • 100% Tested • Available in black jacket only

#### **PRO SERIES**

Part No.	Length
PR809FME	9 FT
PR812FME	12 FT
PR818FME	18 FT

#### **RG59 CO-PHASE CABLE**

HIGH QUALITY RG59 • Bare copper stranded center conductor • High quality soldered PL259 or lug connectors • 95% bare copper braid • Polyethylene dielectric • Hand soldered connections • 100% Tested • Replace (P) with (L) to end of model number for lug connector • Available in black jacket only

#### **PRO SERIES**

Part No.	Length
DH9P	9 FT
DH12P	12 FT
DH18P	18 FT
DH21P	21 FT



MADE IN

S

MADE IN

U. S. A

## RG59 CO-PHASE CABLE W/ REMOVABLE PL259

HIGH QUALITY RG59 • Bare copper stranded center conductor • High quality soldered PL259 on one end and female FME connectors on the other • High quality FME to UHF adapters (NIP-13) included • 95% bare copper braid • Polyethylene dielectric • Hand soldered connections • 100% Tested • Replace (N13) with (FME) to exclude the NIP-13 adapter • Available in black jacket only

Part No.	Length
DH9N13	9 FT
DH12N13	12 FT
DH18N13	18 FT

### TERMINATOR SERIES RG58 CABLE

ProComm's patented Terminator connector • 18 Feet of high quality RG58 cable with PL-259 (UHF) connector or NIP-13 (FME to UHF) adapter • Chrome plated hex nut accepts standard 3/8-24 thread antennas

#### TERMINATOR SERIES

Part No.	Length
HS818T-PL	18 FT W/PL259
HS818T-NKT	18FT W/NIP-13



### STANDARD RG58 CABLE -MOLDED ENDS

RG58 • Bare copper center conductor • Molded PL259 or lug connectors • bare copper braid • Polyethylene dielectric • Replace (PL) with (L) to end of model number for lug connector • Available in black jacket only

#### - HIGH SPEC -IMPORTED

Part No.	Length
HS803PL	3 FT
HS806PL	6 FT
HS809PL	9 FT
HS812PL	12 FT
HS818PL	18 FT

# CO-PHASE RG59 CABLE -MOLDED ENDS

RG59 • Bare copper center conductor • Molded PL259 or lug connectors • bare copper braid • Polyethylene dielectric • Replace (P) with (L) to end of model number for lug connector • Available in black jacket only

#### - HIGH SPEC -IMPORTED

Part No.	Length
HSDH9P	9 FT
HSDH12P	12 FT
HSDH18P	18 FT

